

Specifications

Name	Method	Unit	Min	Max
Centene #	EN 15195	-	51	
Centene Index	EN ISO 4264	-	46	
Density at 15 °C	EN ISO 12185	g/mL	0.820	0.845
Polycyclic Aromatic Hydrocarbons	EN 12916	mass %		8
Sulphur (S)	EN ISO 20884	mg/kg		10
Manganese (Mn)	EN 16576	mg/L		2
Flash Point (PM)	EN ISO 2719	°C	55	
Carbon Residue Micro (10% bot.)	EN ISON 10370 / 3405	mass %		0.3
Ash	EN ISO 6245	mass %		0.01
Water by Karl Fisher	EN ISO 12937	mg/kg		200
Total Contamination	EN 12662	mg/kg		24
Coper Strip Corrosion (3hrs / 50 °C)	EN ISO 2160	-		1
FAME content	EN 14076	vol %		7
Oxidation Stability	EN ISO 12205	g/m3		25
Lubricity	EN ISO 12156-1	µm		460
Kinematic Viscosity at 40 °C	EN ISO 3104	mm ² /s	2.0	4.5
Distillation	EN ISO 3405			
95% Recovered		°C		360
Recovered at 250 °C		vol %		65
Recovered at 350 °C		vol %	85	
Cold Filter Plugging Point	EN 116	°C		-15